


### DP-8130 Options

## **DP-8130 Specifications**

#### STANDARD CONFIGURATION

Copying Process	Indirect Electrostatic Photographic Method
Developing System	2-component Magnetic Brush Developing
Paper Exit	Face Down
Multi Copy Speed*1	Up to 81 cpm (Letter)
Original Scanner Speed*1	65 OPM (Letter)
First Copy Out Time	Approximately 3.2 seconds
Warm-Up Time (20°C)	Approximately 160 seconds
Photoconductor	OPC Drum
Hard Disk Drive	10 GB
Memory	32 MB
Document Storage	24 Locations
Maximum Original Size	Ledger
Maximum Copy Size	Ledger
Paper Weight	17 - 110 lb Index (Drawer and Bypass feeding)
Specialty Paper	Tab Paper from Bypass and Lower Drawer
Paper Feed	Tandem LCF: Letter 2,500 Sheets, Drawers: 500 Sheets x 2,
	Bypass: 100 Sheets
	Maximum 7,600 Sheets with option
Zoom	25 - 400 % (in 1 % increments)
Resolution	600 x 2400 dpi with smoothing
Multiple copy	Up to 9,999 copies
Exposure Control	Automatic plus manual selection from 11 exposure steps
Dimensions (W x D x H)*2	27.5" x 30.6" x 47.8" (698 x 777 x 1,213 mm)
(Excluding optional equipment)	
Weight*2	Approximately 472 lb (214 kg)
Power Consumption	Maximum 2.0 kW (115V) 20A



#### DA1GL1020 CONTROLLER

Processor	Intel® Celeron, 566 MHz
Memory	256 MB Standard/Maximum
Hard Disk Drive	20 GB HDD
DA1GL1020 Scanning	Standard Scan-to-File, Scan-to-Email, Scan-to-TWAIN, Scan-to-Internet Fax
Interfaces	USB, 10/100BaseT Ethernet
Languages	PCL6 Emulation, PostScript 3 Emulation Standard
Network Support	NetWare® 4.x (Bindery), NetWare® 4.x (NDS) including NDPS,
	NetWare® 5.x (Bindery) including NDPS, Windows® NT 4.0 Domain Server,
	4.0, Terminal Server, Windows® 2000 Server, Advanced Server, Windows Server 2003
Peer-to-Peer	Windows® 98SE, Me, 2000 Professional, XP Home/Professional, Server 2003,
	Windows® NT 4.0 Workstation
Network Protocols	IPX/SPX, TCP/IP, EtherTalk®
IP Addressing	Static IP, Auto IP (DHCP)
SNMP/MIB Access	MIB-2 (RFC1213), Host Resource MIB (RFC1514), Printer MIB (RFC1759),
	SNMPv2 traps Printer MIB (RFC1759), SNMPv2 traps
Printing Protocols	Windows® Printing (SMB), LPR/LPD, IPP (v1.1), NetWare® P-Server with NDS and
	with Binary, EtherTalk®, Port 9100 RAW
Windows® Drivers	Windows® 98SE, Me, 2000, Server 2003, XP Home/Professional, Windows® NT 4.
Macintosh® Driver	Mac® OS 8.5 — 10.3 via Mac® PPD for LaserWriter®
UNIX® Filter	Sun® Solaris (v2.5x/2.6/7.0), HP-UX, AIX (IBM) 4.3x, Linux Redhat 7.x

#### ISO 9001 Quality Management System

Management System
Our business produce document,
information and network products, from
manufacturing to marketing, conform to ISO9001
Ouality Management Systems standard. Design,
development, manufacture, installation, repair and
maintenance of document, information and network
products, their associated devices and
consumables. In addition, the plants ousfde Japan
have acquired ISO 9001 certification.





As an Energy Star® partner, Panasonic has determined that this product meets the Energy Star® guidelines for energy efficiency.

# **Panasonic**